

**What is claimed is:**

- [illegible]

7. The light-emitting-diode chip package according to claim 1, wherein the light-emitting-diode chips include a light-emitting-diode chip that emits blue light, a light-emitting-diode chip that emits green light, and a light-emitting-diode chip that emits red light.
8. The light-emitting-diode chip package according to claim 1, wherein the array of light-emitting-diode chips produces a single unit of white light.
9. The light-emitting-diode chip package according to claim 1, wherein the collimator is generally configured as a rectangular, horn-like member.
10. The light-emitting-diode chip package according to claim 9, wherein the collimator includes a first set of walls that collimate the light emitted by the light-emitting-diode chips in a first direction and a second set of walls that minimally collimate the light emitted by the light-emitting-diode chips in a second direction.
11. The light-emitting-diode chip package according to claim 1, wherein the collimator includes a first set of walls that collimate the light emitted by the light-emitting-diode chips in a first direction and a second set of walls that minimally collimate the light emitted by the light-emitting-diode chips in a second direction.
12. The light-emitting-diode chip package according to claim 1, wherein the base is adapted for bonding lead wires.

10083328 102201

13. A light source comprising:  
at least two light-emitting-diode chip packages;  
each of the light-emitting-diode chip packages including:  
a base;  
an array of light-emitting-diode chips disposed on the base; and  
a collimator mounted on the base, over the array of light-emitting-diode chips.
14. The light source according to claim 13, wherein the light-emitting-diode chips are arranged in each of the arrays in an inline manner.
15. The light source according to claim 13, wherein each of the arrays of light-emitting-diode chips includes a light-emitting-diode chip that emits blue light, a light-emitting-diode chip that emits green light, and a light-emitting-diode chip that emits red light.
16. The light source according to claim 13, wherein each of the arrays of light-emitting-diode chips produces a single unit of white light.
17. The light source according to claim 13, wherein each of the collimators is generally configured as a rectangular, horn-like member.
18. The light source according to claim 13, wherein each of the collimators includes a first set of walls that collimate the light emitted by their respective light-emitting-diode

1008388 102201 82E800T

chips in a first direction and a second set of walls that minimally collimate the light emitted by their respective light-emitting-diode chips in a second direction.

19. The light source according to claim 13, wherein each of the bases is adapted for bonding lead wires.

10083328 102201 822201 822201